

Portable Electric

Dealer Hot Water Pressure Washers







Designed for heavy-duty industrial cleaning jobs requiring hot water, the belt-driven HHB Series can easily handle demanding jobs. It is a popular choice on construction jobsites, agricultural locations and for indoor commercial cleaning applications.

Pump:

Belt drive triplex piston AR pump with ceramic plungers Adjustable high pressure detergent injector

Motor:

Open drip-proof electric motor with manual thermal overload protection 35-foot power cord

Frame:

Wrinkle-finish powder coated steel frame assembly | 13-inch flat-free tires with rear tire brake

Components:

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) Racor fuel filter/water separator Adjustable thermostat Polyethylene float tank with inlet filter screen 10-gallon polyethylene fuel tank

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and low pressure nozzle (except on HHB-303-0E1A) | 50-foot x %-inch high pressure hose (50-foot steam hose on HHB-303-0E1A) | Adjustable pressure insulated dual lance (except on HHB-303-0E1A) | Single lance with dual insulated grips; steam nozzle (HHB-303-0E1A) | Professional-grade insulated trigger gun with safety lock-off





