

Stationary Natural Gas/LP

Dealer Hot Water Pressure Washers



Even the most demanding cleaning jobs are no match for the super-efficient, high volume HEG series. Designed to tackle heavy soil and solid dirt, oil and even the worst grease, choose from either a 2000 or 3000 PSI model.

Pump:

Belt drive triplex piston General pump with ceramic plungers

Motor:

Open drip-proof electric motor with manual thermal overload protection

Frame:

Powder coated steel frame and removable side panels

Components:

½-inch schedule 80 pipe coil with 8-pancake heat exchanger (¾-inch on HEG-2010 models)

Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 12-inch stack

Electronic ignition with intermittent pilot

Adjustable outlet thermostat for main temperature control

Polyethylene float tank (8-gallon with in-line screen filter)

Time delay shutdown

Miscellaneous:

Unique coil design allows thermostat to sense upstream water temperature to regulate outlet temperatures preventing large temperature swings Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and fixed detergent nozzle | 50-foot x %-inch steel wire-braided high pressure hose (½-inch on HEG-2010 models) | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off





