

Stationary Oil-Fired

Dealer Hot Water Pressure Washers

HEO Series — Belt Drive





HEO-3004-0E3G shown with fuel tanks option, HX-0218

Designed as a stationary unit with removable side panels, this efficient hot water pressure washer is the perfect solution if you are looking for a wash bay system. The powder coated steel frame makes it extremely durable under tough conditions.

Pump:

Belt drive triplex piston General pump with ceramic plungers | Thermal relief valve Adjustable high pressure detergent injector

Motor:

Open drip-proof electric motor with manual thermal overload protection

Powder coated steel frame and removable side panels

Components:

1/2-inch schedule 80 pipe coil with 5-pancake heat exchanger 10-inch draft diverter On/Off burner, pump and motor switches Pressure switch and over-pressure safety controls 24V control system Polyethylene float tank (4-gallon with in-line screen filter) Adjustable thermostat

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option) Designed to run on an existing fuel tank (Optional fuel tanks available)

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and fixed detergent nozzle 50-foot x %-inch steel wire-braided high pressure hose Adjustable pressure insulated dual lance Professional-grade insulated trigger gun with safety lock-off





